

YANTON®

PROFESSIONAL FM TRANSCEIVER

T-S6 / T-S8

MAIN FEATURE

- Frequency Range: 400-480MHZ 16 Memory Channels
- Output Power 3W
- Support non-standard CTCSS/DCS
- Side keypad assignment
- Flashlight
- Vox Function



SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	400~480MHz	RF Power	3W
Operating Temperature	-20°C~+60°C	Modulate Mode	F3E
Frequency Combination	Phase lock frequency synthesize	Max. Freq. Deviation	≤5K
Frequency Stability	±2.5ppm	Remain Wave Radiation	<-60dB
Memory Channel	16 Channels	Transmitting Current	≤1000mA
Working voltage	DC 3.7V	RECEIVE PART	
Battery capacity	1000mAH Li-ion Battery	Sensitivity	<0.25µV(12dB SINAD)
Antenna Impedance	50Ω	Squelch Sensitivity	<0.20µV
Operating Mode	Simplex of co-frequency or alien	Intermodulation Antijamming	50dB
	frequency	Audio Power output	500mW
Dimension	89×49×31mm (without volume knob)	Receiving Current	≤100mA
Weight	150g (Include Battery Pack)	Squelch Standby	20mA

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.

QUANZHOU YANTON ELECTRONICS CO.,LTD. http://www.yantonradio.com